

KEY OR ELECTRONIC LOCK

MODEL SHOWN: TRIDENT DUOFORCE T2 GRADE V M-245

TRIDENT DF T2 GRADE V

BURGLARY & FIRE-RESISTANT PROTECTION

RATINGS: CASH £100,000 • VALUABLES £1,000,000

KEY FEATURES

- Burglary resistance in accordance with the updated and more stringent European standard, EN 1143-1:2019 T2, as certified by ECB•S for Grade V.
- Supplied with two locks as standard with the option of a factory-fitted electronic lock. This gives the flexibility to customise how DuoForce T2 can be secured and operated.
- Ergonomic soft-touch handle and a range of internal fittings to maximise storage capacity.
- EN 1143-1:2019 is the latest version of this globally respected burglary resistant standard. The new T2 classification includes tests with the more powerful and effective versions of the tools available to burglars today: Power tools, grinders, cutters and thermal tools have upgraded performance over earlier models. DuoForce T2 models provide protection against current and foreseeable future threats.
- Tested by an independent, ISO 17025 accredited laboratory according to the NT Fire 017 – 60 Paper standard with certification managed by ECB•S. Protects your vital documents from the effects of fire.



PRODUCT SPECIFICATIONS

| Model | External Sizes (mm) | | | Internal Sizes (mm) | | | Volume (litres) | Weight (kg) | Shelves Included |
|--------|---------------------|-------|-------|---------------------|-------|-------|-----------------|-------------|------------------|
| | Height | Width | Depth | Height | Width | Depth | | | |
| M-65 | 739 | 574 | 584 | 555 | 390 | 303 | 65 | 577 | 1 |
| M-95 | 974 | 574 | 584 | 790 | 390 | 303 | 95 | 727 | 2 |
| M-245 | 974 | 824 | 764 | 790 | 640 | 483 | 245 | 1137 | 2 |
| M-405 | 1494 | 824 | 764 | 1310 | 640 | 483 | 405 | 1588 | 3 |
| M-520 | 1874 | 824 | 764 | 1690 | 640 | 483 | 520 | 1993 | 4 |
| M-885 | 1874 | 1274 | 764 | 1690 | 1090 | 483 | 885 | 2766 | 4 |
| M-1090 | 1874 | 1524 | 764 | 1690 | 1340 | 483 | 1090 | 3180 | 4 |

External dimensions exclude handle and hinge projections. In line with certification, weights can vary by +/- 5%.